

16 mm



CHILD SAFETY
EN13120

BLIND COST € 74,00 PER SQM

The 16mm Venetian blind is a cord and rod operated blind for orientation. The slats are in 16 mm aluminum with a 25x24 mm box and a 20x10 mm terminal. The SLIM version is equipped with the same slats and terminal but with a 20 mm box (see section increase by price). For indoor environments only.

AS STANDARD

ATTACHMENT: wall and/or ceiling.

CONTROL SIDE: right side rope and left side rod.

RECOMMENDED DIMENSIONS: max 5 m².

MINIMUM WIDTH: 26 cm maximum 230 cm.

MINIMUM HEIGHT: 26 cm maximum 250 cm.

ON REQUEST WITHOUT SURCHARGE

CONTROL SIDE: of your choice to be specified in the order.

SLIM BOX

MINIMUM WIDTH: 26 cm maximum 200 cm.

MINIMUM HEIGHT: 26 cm maximum 220 cm.

NOTES

- Curtains less than 16 cm: fixed, without command +100%;
- Curtains less than 26 cm: Command available with central orienter +60%;
- Blinds from 26 to 40 cm: Standard or reverse control;
- Minimum billable 1.5 sqm;
- Standard cleat and anti-noose;
- Dowels and screws are not included.

SUPPLEMENTS

- Metallic finishes +10%;
 - Perforated finishes +25%;
 - Printed finishes +50%;
 - Curtains in two colors +10%, in three colors +15%.
- For other colors ask for a quote.
- The SLIM box is available in different colours: white, gray, beige, black and brown (+15%).
 - Decentralized and/or non-standard commands €10 per tent
 - For venetian blinds with additional guide + 5%


MOTORS AND POWER SUPPLIES - PAGE 213

RTS TRANSMITTERS - PAGE 214


HOME AUTOMATION - PAGE 215

ACCESSORIES - PAGES 216, 217, 218


CEILING AND/OR WALL MOUNTING



**VIEW
FROM THE SIDE**
Installation on wall



**VIEW
FROM THE SIDE**
Installation on ceiling



CONCEALED ATTACHMENT


ON REQUEST
WITHOUT SURCHARGE



STANDARD COMMANDS




NORMAL
Right side rope and
left side rod




REVERSE
Left side rope and
right side rod

GROUPED COMMANDS




**RIGHT
CONTROLS**
width min.40 cm




**LEFT
CONTROLS**
width min.40 cm

DIMENSIONS



HEIGHT HI
HT = packed
awning height



HEIGHT HT
HT = descending
awning height

BULGE A+P
16 mm = 4 cm
16 mm Slim = 3,5 cm

DIMENSIONS (MEASUREMENTS IN CM)

	50	100	150	200	250	300
HEIGHT HT	5,1	6,9	8,7	10,5	12,3	14,1
HI SLIM	4,8	7,1	9,4	11,7	14	16,3

**VENETIAN
16**

**VENETIAN
16 SLIM**

BOX



SLATS



TERMINAL CAPS



STD HEIGHT OF PLEXIGLASS ROD (CM)	
VENETIAN HEIGHT	H ROD/ROPE
Up to 100 cm	50
From 101 cm to 230 cm	100
Over 231 cm	150