


# MAX

MAXIMUM DIMENSIONS - W400 X H400 CM


## STANDARD

**BRACKET:** White painted metal with side cover and PVC screw caps. Reinforced 6060 alloy aluminium tube, 70 mm diameter.  
**CHAIN:** Continuous loop white PVC.  
**PVC ACCESSORIES:** White; black and grey available on request.  
**OPERATION:** 4:1 gear reduction, right-hand side, with continuous loop chain.

## CEILING AND/OR WALL MOUNTING




**SIDE VIEW**  
Ceiling fixing



**SIDE VIEW**  
Wall fixing


### FRONT VIEW

For the chain system, the fabric width is calculated by **SUBTRACTING 61 mm** from the requested width.




### CENTRAL BRACKET FOR TWO BLINDS


Fabric deduction:  
**SUBTRACTING 61 mm** per blind.




## FABRIC DROP DIRECTION




Outside the room  
AS STANDARD




Inside the room  
ON REQUEST




**TUBE INSERT (FIG.1)**  
For roller with PVC insert welded to the fabric



**CHAINS**  
Continuous loop chain    Chain with connector



**TEARDROP BOTTOM BAR**  
Standard, with insert welded to the fabric.



**POCKET HEM BAR**  
Teardrop pocket, on request, where applicable on the fabric.  
NO EXTRA CHARGE.



## AVAILABLE FINISHES



Glossy white  
RAL 9010



Black  
RAL 9005



Satin aluminium

## NOTES

- All fabrics are welded with the PVC insert and slide-fitted into the ogive tube (FIG.1);
- Wall plugs and screws not included.

## OPTIONAL

**IBOX TECHNICAL DATA SHEET - PAGE 101**  
**CABLE GUIDE AND SIDE GUIDE TECHNICAL DATA SHEET**  
**PAGES 103-104**  
**MOTORS AND CONTROLLERS - PAGES 119-123**  
**ROLLER BLIND OPTIONAL ACCESSORIES - PAGE 125**

### CHAIN LENGTHS

- From 0 to 250 cm: Chain length = blind height - 10 cm (connector included);
  - From 251 to 300 cm: continuous loop chain 250 cm.
  - From 301 to 350 cm: continuous loop chain 300 cm;
- NOTE:** For custom chain lengths, only metal chain is available.